

# LIND



## DUAL USB-A AND USB-C OUTPUT ADAPTER

Model # USBC2-5662 (1 USB-A and 1 USB-C)  
Model # USBC2-5834 (2 USB-C)

### MODERN POWER, THE LIND WAY.

The Lind dual universal USB-C adapter is a dual USB-C output DC/DC adapter that allows you to **simultaneously charge up to two low-power devices** (tablets, phones, digital cameras and other mobile devices) in a **cost-effective, durable design**. Simply plug the USB-C cable from your connected device(s) into one of the universal USB-C or USB-A ports on the adapter. The left port delivers 15W of power and the right port delivers up to 45W of power via USB-PD (depending on device needs).

The dual USB-C adapter will filter voltage spikes or surges on the input, protecting the downstream device from damage. The adapter is completely sealed with an epoxy potting material, protecting all critical components from shock, vibration, dust, and water ingress. These adapters are engineered to take on the toughest conditions to keep your device powered for years of use - no matter the challenge or environment.

### RUGGED ISN'T A FEATURE, IT'S THE STANDARD!

For more information on our portfolio of power adapters or any of our other products, please visit us at [www.lindelectronics.com](http://www.lindelectronics.com).



(952) 927-6303  
(800) 897-8994

14850 Deveau Place  
Minnetonka MN 55345

[LindElectronics.com](http://LindElectronics.com)

### FEATURES

- ✓ **DUAL OUTPUTS** – USB-A/USBC port (15W max) and USB-C port power delivery (up to 45W)
- ✓ **USB-C POWER DELIVERY** – Supports 5V/9V/15V/20V up to 2.25A
- ✓ **12V DC INPUT** – Compatible with standard 12V and 24V battery applications (12-32V input)
- ✓ **COMPACT & RUGGED DESIGN** – Ideal for automotive, RV, and embedded use
- ✓ **COMPREHENSIVE PROTECTION** – Over-voltage, over-current, thermal, and short-circuit safeguards
- ✓ **LED INDICATOR** – Displays input power, charging, and fault status
- ✓ **THERMAL MANAGEMENT** – Efficient heat dissipation for stable performance

### TECHNICAL SPECS

- ⚡ **INPUT VOLTAGE:** 12-32 VDC
- ⚡ **INPUT CURRENT DRAW:** 6.25A max
- ⚡ **INPUT FUSE:** Includes 8A inline 3AG fuse
- ⚡ **OUTPUT POWER:**
  - USB-A/USBC: 5V @ 3A (15W)
  - USBC power delivery: 5V/9V/15V @ 3A, 20V @ 2.25A (45W max)
- ⚡ **DIMENSIONS (APPROX):** 2.75 x 2.25 x 1.0 inches (6.99 x 5.72 x 2.54 cm)
- ⚡ **WEIGHT (APPROX):** 0.6 lbs (0.27 kg) excluding cables
- ⚡ **OPERATING TEMP:** -20 to +40° C
- ⚡ **STORAGE TEMP:** -40 to +85° C

